

R 410A SERIES 10 JOHNSON CONTROLS



r 410a series 10 pdf

Eubanks www.nationalcoilcompany.com/eubank.html V and H Series A/C and H/P ~ R-410A 10.0 SEER - V Series - High Efficiency Wall-Mount Air Conditioners – R-22

Eubanks www.nationalcoilcompany.com/eubank.html V and H

View and Download Goodman R-410A installation manual online. R-410A OUTDOOR SPLIT-SYSTEM HEAT PUMP, 13 SEER & 14.5 SEER 1.5 TO 5 TONS – 1 & 3 PHASE. R-410A Heat Pump pdf manual download. Also for: Thgd series, Thgf series, Ghgd series, Thjd series, Thjf series, Yhjd series, Yhjf...

GOODMAN R-410A INSTALLATION MANUAL Pdf Download.

528194-YTG-D-0610 Johnson Controls Unitary Products 3 Nomenclature Z F 090 N10 A 2 A AA 4 0 1 2 4 A Product Category Z = A/C, Single Pkg., R-410A A = Std. Motor

TECHNICAL GUIDE Description R-410A ZF/ZR SERIES

View and Download Daikin R-410a owner's manua online. 60hz. R-410a Air Conditioner pdf manual download.

DAIKIN R-410A OWNER'S MANUA Pdf Download.

570568-YIM-A-0310 4 Johnson Controls Unitary Products Product Nomenclature Z F 048 N04 A 2 A AA 1 0 1 2 4 A Z = A/C, Single Pkg., R-410A X = HP, Single Pkg., R-410A

R-410A ZF SERIES - UPGNET

refrigerant (R-410A) provide excellent part-load performance in a compact package, while meeting or exceeding ASHRAE 90.1 minimum energy efficiency requirements.

Selection Guide Aqua Series Air-Cooled Chillers 10 to 500 Tons

Form No. S3502-219 Supersedes S3502-1018 Page 2 of 20 Capacity is certified in accordance with ANSI/ARI Standard 390-2003. EER = Energy Efficiency Ratio and is certified in accordance with ANSI/ARI Standard 390-2003.

Green r Models W42LA to W72LB Left-Side Control Panel r

7 REFRIGERANT CHARGE ADJUSTMENTS Liquid Line Size R---410A Charge oz/ft 3/8 0.60 (Factory charge for lineset = 9 oz) 5/16 0.40 1/4 0.27 Units are factory charged for 15 ft (4.6 m) of 3/8" liquid line.

Product Data - dms.hvacpartners.com

SG-BAH-20 June 2017 Specification Guide B Series Multi-Position & Hydronic Air Handlers Electric or Hot Water Heat, with available Variable-Speed High Efficiency ECM Motor

B Series Spec Guide (SG-BAH-20) - adpnow.com

EDUS391000-F1 Specifications FXFQ-P 3 Ceiling Mounted Cassette Type (Round Flow) Notes: 1 Nominal cooling capacities are based on the following conditions: Return air temperature: 80°FDB(27°CDB), 67°FWB(19.4°CWB)

FXFQ-P Ceiling Mounted Cassette Type (Round Flow)

Dat a s h e e t HP Color LaserJet Pro MFP M477 series St u n n i n g s p e e d . S o l i d s e c u r i t y . U n m a t c h e d p r i n t , s c a n , c o p y , a n d f a x p e r f o r m a n c e p l u s r o b u s t , c o m p r e h e n s i v e s e c u r i t y f o r h o w y o u w o r k .

series HP Color LaserJet Pro MFP M477

PRODUCT SPECIFICATIONS Split System Heat Pump: WCH5**4 6 Specifications subject to change without notice. 428 55 7200 04 R-410A COOLING CAPACITY LOSS FOR VARIOUS LINE LENGTHS & TUBE DIAMETERS Model Size Liquid Line

WCH54 - grandaireac.com**

Components SAE 45° - BRASS FLARED TUBE FITTINGS © 2014, ENALT 50-12/2014 sup. 03/2014-8-E2- 5 E2- 8 E2- 6 E2-10 Male SAE Flare x Female NPT National Pipe Thread ELL

HVAC&R 45° SAE Flare Brass Fittings - ENALT

13 Single phase Fuse type DC to AC & Linear control Solid State Module Specification Rated current corresponding to Resistive load I Type Model

www.fotek.com.tw

7.2 Heating Capacity 12 18

FXAQ-PVJU Wall Mounted Type - Daikin AC

AHRI Certified, ETL Listed Environmentally-friendly R-410A refrigerant Great for new construction or retrofit

Products - SKYMARK

Liquid Line. Quick Selection Recommendations. Bulletin 40-10 – Page 3 *C-30000 and C-40000 Series shells are not approved for R-410A. SYSTEM SIZE FIELD REPLACEMENT

Liquid & Suction Line Filter-Driers - Sporlan Online

Catalog 201 Condensed Catalog of Sporlan Products May 2011 / Catalog 201

May 2011 Catalog 201 - Sporlan Online

7 5 SERIES 500A11 INSTALLATION MANUAL General Installation Information cont. @WUVb:STb! & BV`SORSR @]R Pg]bVS`a 6Sf <cba Pg]bVS`a EOaVS` DWP`ObW]\